

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name:	HWY DYED DIESEL #2 15 MV

Manufacturer Information:

Sunoco, Inc. (R&M) 1735 Market Street LL

Philadelphia, Pennsylvania, 19103-7583

Product Use:

Diesel fuel

Emergency Phone Numbers:

Chemtrec	(800) 424-9300
Sunoco Inc.	(800) 964-8861

Information:

Product Safety Information (888) 567-3066

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
#2 DIESEL HIGHWAY	68476-34-6	100 - 100
NAPHTHALENE	91-20-3	0 - 2
XYLENE	1330-20-7	0 - 0.8
TOLUENE	108-88-3	0 - 0.4
BENZENE	71-43-2	0 - 0.2
ETHYL BENZENE	100-41-4	0 - 0.2
CUMENE	98-82-8	0 - 0.1
N-HEXANE	110-54-3	0 - 0.04

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	CAS No.	Governing Body	Exposure Limits		
Limit for the product	68476-34-6	ACGIH	TWA	100	mg/m3
BENZENE	71-43-2	ACGIH	STEL	2.5	ppm
BENZENE	71-43-2	OSHA	STEL	5	ppm
BENZENE	71-43-2	ACGIH	TWA	0.5	ppm
BENZENE	71-43-2	OSHA	TWA	1	ppm
CUMENE	98-82-8	ACGIH	TWA	50	ppm
CUMENE	98-82-8	OSHA	TWA	50	ppm
ETHYL BENZENE	100-41-4	ACGIH	STEL	125	ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA	100	ppm
ETHYL BENZENE	100-41-4	OSHA	TWA	100	ppm
N-HEXANE	110-54-3	ACGIH	TWA	50	ppm
N-HEXANE	110-54-3	OSHA	TWA	500	ppm

NAPHTHALENE	91-20-3	ACGIH	STEL	15	ppm
NAPHTHALENE	91-20-3	ACGIH	TWA	10	ppm
NAPHTHALENE	91-20-3	OSHA	TWA	10	ppm
TOLUENE	108-88-3	NIOSH	STEL	150	ppm
TOLUENE	108-88-3	ACGIH	TWA	20	ppm
TOLUENE	108-88-3	OSHA	TWA	200	ppm
XYLENE	1330-20-7	ACGIH	STEL	150	ppm
XYLENE	1330-20-7	ACGIH	TWA	100	ppm
XYLENE	1330-20-7	OSHA	TWA	100	ppm
#2 DIESEL HIGHWAY	68476-34-6	ACGIH	TWA	100	mg/m3

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Warning! Combustible liquid and vapor. Harmful if inhaled. May cause headaches and dizziness. Harmful if absorbed through skin. Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage. Causes skin irritation. Can cause severe chronic toxicity. Possible cancer hazard.

Hazards Ratings:

Key: $0 = least$, $1 = slight$, 2	= moderate	, 3 = high, 4	4 = extreme	
	<u>Health</u>	Fire	Reactivity	<u>PPI</u>
NFPA	1	2	0	
HMIS	2	2	0	Х

POTENTIAL HEALTH EFFECTS

PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, nervous system, respiratory system, lung (asthma-like conditions),

INHALATION

Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. May cause headaches and dizziness. Repeated excessive exposures may cause blood disorders such as anemia and leukemia. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death).

LC50 (mg/l):	No data
LC50 (mg/m3):	No data
LC50 (ppm):	No data

SKIN

May be absorbed through the skin in harmful amounts. Contains a material that has caused skin tumors in laboratory animals. Causes severe skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Draize Skin Score:6.9out of 8.0

LD50 (mg/kg): No data

EYES

Mildly irritating to the eyes.

INGÉSTION

Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage.

LD50 (g/kg): No data

4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

SKIN

Wash with soap and water for 20 minutes. Get medical attention if irritation develops or persists. Wash clothing before reuse. Destroy contaminated shoes and other leather products.

EYES

Flush eye with water for 20 minutes. Get medical attention.

INGESTION

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray; Regular foam; Dry chemical; Carbon dioxide;

FIRE FIGHTING INSTRUCTIONS

Use water spray to cool fire exposed tanks and containers. Water or foam may cause frothing. Wear structural fire fighting gear. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				> 125	F	PMCC
Autoignition Temperature	500				F	N/A
Lower Explosion Limit				No data	%	N/A
Upper Explosion Limit				No data	%	N/A

6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

HANDLING

Use only in a well-ventilated area. Ground and bond containers when transferring material. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. **STORAGE**

Keep away from heat, sparks, and flame. Keep container closed when not in use. NFPA class II storage. Flash point is greater than 100 degrees F and less than 140 degrees F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

ENGINEERING CONTROLS

Use with adequate ventilation. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTION

EYE PROTECTION

Splash proof chemical goggles are recommended to protect against the splash of product.

GLOVES or HAND PROTECTION
Protective gloves are recommended when prolonged skin contact cannot be avoided. The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Polyvinyl chloride (PVC); Neoprene; Nitrile; Polyvinyl alcohol; Viton;

RESPIRATORY PROTECTION Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Respiratory protection is not usually needed unless product is heated or misted.. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a positive pressure-demand full-face poster levels are unknown, then use a postive pressure-demand full-face poster levels are unknown, then use a postive pressure-demand full-face poster levels are unknown, then use a postive pressure-demand full-face poster levels are unknown, then use a postive pressure-demand full-face poster levels are unknown at the postive pressure demand poster levels poster

OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: Polyvinyl alcohol (PVA); Polyvinyl chloride (PVC); Neoprene; Nitrile; Viton; Polyurethane; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse.

Physical Property	Typical	Units	Text Result	Reference
Appearance		other	Lt Amber Liquid	
Boiling Point		F		
Bulk Density		lb/gal	No data	
Melting Point		F	No data	
Molecular Weight		g/mole	No data	
Octanol/Water Coefficient		other	No data	
рН		other	No data	
Specific Gravity	0.87	other		
Solubility In Water		wt %	Nil	
Odor		other	Kerosene-like	
Odor Threshold		other	No data	
Vapor Pressure	1.6	mmHg		
Viscosity (F)		other	No data	
Viscosity (C)	1.9	CsT		
% Volatile		wt %	No data	

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

STABILITY Stable CONDITIONS TO AVOID Avoid heat, sparks and open flame. INCOMPATIBILITY Cutting oil Strong oxidizers HAZARDOUS DECOMPOSITION PRODUCTS Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants. Will not polymerize.

11. ECOLOGICAL INFORMATION

No data available

12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

13. TRANSPORT INFORMATION

Governing Body IATA DOT	<u>Mode</u> Air Ground	Proper Shippin Not Determined Fuel Oil		
<u>Governing Body</u>	Mode	Hazard Class	<u>UN/NA No.</u>	<u>Label</u>
ΙΑΤΑ	Air	Not Determined		
DOT	Ground	Combustible Liquid	NA1993	

14. REGULATORY INFORMATION

Regulatory List	Component	CAS No.
ACGIH - Occupational Exposure Limits - TWAs	ULSD #2 15 MOTOR VEHICLE	68476-34-6
Inventory - Canada - Domestic Substances List	ULSD #2 15 MOTOR VEHICLE	68476-34-6
Inventory - China	ULSD #2 15 MOTOR VEHICLE	68476-34-6
Inventory - European EINECS Inventory	ULSD #2 15 MOTOR VEHICLE	68476-34-6
Inventory - Philippines Inventory (PICCS)	ULSD #2 15 MOTOR VEHICLE	68476-34-6
Inventory - TSCA - Sect. 8(b) Inventory	ULSD #2 15 MOTOR VEHICLE	68476-34-6
New Jersey - Env Hazardous Substances List	ULSD #2 15 MOTOR VEHICLE	68476-34-6
ACGIH - Occupational Exposure Limits - Carcinogens	#2 DIESEL HIGHWAY	68476-34-6
ACGIH - Occupational Exposure Limits - Carcinogens	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - Carcinogens	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - Carcinogens	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - Carcinogens	XYLENE	1330-20-7
ACGIH - Occupational Exposure Limits - TWAs	#2 DIESEL HIGHWAY	68476-34-6
ACGIH - Occupational Exposure Limits - TWAs	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - TWAs	CUMENE	98-82-8
ACGIH - Occupational Exposure Limits - TWAs	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - TWAs	N-HEXANE	110-54-3
ACGIH - Occupational Exposure Limits - TWAs	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - TWAs	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - TWAs	XYLENE	1330-20-7
ACGIH - Short Term Exposure Limits	BENZENE	71-43-2
ACGIH - Short Term Exposure Limits	ETHYL BENZENE	100-41-4
0000224602 HWW DVED DIECEL #2 15 MW		F

ACGIH - Short Term Exposure Limits ACGIH - Short Term Exposure Limits ACGIH - Skin Absorption Designation CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - Organic HAPs CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA (Clean Air Act) - HON Rule - SOCMI Chemicals CAA - 1990 Hazardous Air Pollutants California - Prop. 65 - Developmental Toxicity California - Prop. 65 - Developmental Toxicity California - Prop. 65 - Reproductive - Male California - Proposition 65 - Carcinogens List California - Proposition 65 - Carcinogens List California - Proposition 65 - Carcinogens List Canada - WHMIS - Ingredient Disclosure CERCLA/SARA - Haz Substances and their RQs CERCLA/SARA - Haz Substances and their RQs

NAPHTHALENE	91-20-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE NAPHTHALENE	110-54-3 91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
TOLUENE BENZENE	108-88-3 71-43-2
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
BENZENE	71-43-2
BENZENE	71-43-2
CUMENE	98-82-8
CUMENE	98-82-8
	98-82-8
ETHYL BENZENE	100-41-4
ETHYL BENZENE	100-41-4
ETHYL BENZENE N-HEXANE	100-41-4 110-54-3
N-HEXANE	110-54-3
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
NAPHTHALENE	91-20-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
TOLUENE	108-88-3
TOLUENE	108-88-3
XYLENE	1330-20-7
XYLENE	1330-20-7
XYLENE	1330-20-7

CERCLA/SARA - Section 313 - Emission Reporting CWA (Clean Water Act) - Hazardous Substances CWA (Clean Water Act) - Priority Pollutants CWA (Clean Water Act) - Toxic Pollutants IARC - Group 1 (carcinogenic to humans) IARC - Group 2B (Possibly carcinogenic to humans) IARC - Group 2B (Possibly carcinogenic to humans) IARC - Group 3 (not classifiable) IARC - Group 3 (not classifiable) Inventory - Australia (AICS) Inventory - Canada - Domestic Substances List Inventory - China Inventory - European EINECS Inventory Inventory - Japan - (ENCS) Inventory - Japan - (ENCS) Inventory - Japan - (ENCS) Inventory - Japan - (ENCS)

BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE NAPHTHALENE	100-41-4 91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE #2 DIESEL HIGHWAY	1330-20-7 68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6 71-43-2
BENZENE CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3

Inventory - Japan - (ENCS) Inventory - Japan - (ENCS) Inventory - Japan - (ENCS) Inventory - Korea - Existing and Evaluated Inventory - Philippines Inventory (PICCS) Inventory - TSCA - Sect. 8(b) Inventory Massachusetts - Right To Know List New Jersey - Department of Health RTK List New Jersey - Env Hazardous Substances List New Jersey - Special Hazardous Substances NTP - Report on Carcinogens - Known Carcinogens NTP - Report on Carcinogens - Suspect Carcinogens **OSHA - Final PELs - Ceiling Limits OSHA - Final PELs - Ceiling Limits** OSHA - Final PELs - Short Term Exposure Limits **OSHA - Final PELs - Skin Notations**

NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
	98-82-8
ETHYL BENZENE	100-41-4
	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
#2 DIESEL HIGHWAY	68476-34-6
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
NAPHTHALENE	91-20-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
CUMENE	98-82-8
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
NAPHTHALENE	91-20-3
BENZENE	71-43-2
TOLUENE	108-88-3
BENZENE	71-43-2
CUMENE	98-82-8
	00 02 0

OSHA - Final PELs - Time Weighted Averages	BENZENE	71-43-2
OSHA - Final PELs - Time Weighted Averages	CUMENE	98-82-8
OSHA - Final PELs - Time Weighted Averages	ETHYL BENZENE	100-41-4
OSHA - Final PELs - Time Weighted Averages	N-HEXANE	110-54-3
OSHA - Final PELs - Time Weighted Averages	NAPHTHALENE	91-20-3
OSHA - Final PELs - Time Weighted Averages	TOLUENE	108-88-3
OSHA - Final PELs - Time Weighted Averages	XYLENE	1330-20-7
OSHA - Regulated Carcinogens	BENZENE	71-43-2
OSHA - Select Carcinogens	BENZENE	71-43-2
Pennsylvania - RTK (Right to Know) List	BENZENE	71-43-2
Pennsylvania - RTK (Right to Know) List	CUMENE	98-82-8
Pennsylvania - RTK (Right to Know) List	ETHYL BENZENE	100-41-4
Pennsylvania - RTK (Right to Know) List	N-HEXANE	110-54-3
Pennsylvania - RTK (Right to Know) List	NAPHTHALENE	91-20-3
Pennsylvania - RTK (Right to Know) List	TOLUENE	108-88-3
Pennsylvania - RTK (Right to Know) List	XYLENE	1330-20-7
Pennsylvania - RTK - Special Hazardous Substances	BENZENE	71-43-2
TSCA - Sect. 12(b) - Export Notification	N-HEXANE	110-54-3
TSCA - Sect. 12(b) - Export Notification	NAPHTHALENE	91-20-3
TSCA - Section 4 - Chemical Test Rules	NAPHTHALENE	91-20-3
TSCA - Section 8(a) - PAIR Reporting List	NAPHTHALENE	91-20-3

Title III Classifications Sections 311,312:

Acute: YES Chronic: YES Fire: YES Reactivity: NO Sudden Release of Pressure: NO

15. OTHER INFORMATION

Follow all MSDS/label precautions even after container is emptied because it may retain product residue. Following injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner or properly disposed of. COMPONENT TOXICITY: Overexposure to naphthalene, a minor component of this product, may cause skin, eye and respiratory tract irritation, anemia, loss of vision, nervous system effects and kidney and thymus damage. Also, exposure to naphthalene has produced "respiratory tract" tumors in laboratory animals..